

General Rules

General Rules

(Revised – Dec. 2014)

ALERT: Tractor & Truck pullers hitch opening size requirements: 3 ¾ inch front to back and 3 inch side to side.

1. Engine must be of same manufacture as tractor with same number of cylinders. Must bolt in manufacturer's intended location without modification.
2. Gas, diesel, or LP fuels only. No fuel additives. No pressurized bottles. American Farm Pullers Association may check fuel at their discretion.
3. No downdraft or fuel injected carburetors. No water injection of any kind. No P pumps in modified stock. Manifolds may be homemade. No headers. (Revised – Dec. 2014)
4. Turbo chargers allowed in Turbo Class only.
5. All tractors must have stock frames, transmissions, and axle housings.
6. Weights, brackets, or any part of the tractor may not extend forward more than 11 feet from the center of the rear axle or rearward past plane of the rear tires. Turbo class is allowed 13 feet from center of axle forward.
7. Drawbar may be no shorter than 18 inches from the centerline of the rear axle to the point of hook and no higher than 20 inches and stationary in all directions with a 3-inch opening in drawbar or clevis.
8. Tractor not required to have PTO.
9. A factory 70 or more horsepower must pull 7500# or above.
10. If 5 or less pullers in a weight class, two entries per tractor allowed, but only one can place.
11. The first puller, who will be the test puller in each class, has the option to keep the pull or drop to third position or last. In pull-off, there will be no test puller.
12. If the puller attempts to stop before the 75-foot mark, the puller will be given one restart.
13. If the tractor touches the boundary line during the pull, except after 300 feet, the tractor will be disqualified.
14. If any weight or part falls to the ground while hooked to the sled, the tractor is disqualified. If due to internal breakage, a measurement will be taken.

15. Tractor & Truck pullers hitch opening size requirements: 3 $\frac{3}{4}$ inch front to back and 3 inch side to side.