

# 8000# Hot One Ton Rules

## 8000 lb. Hot One Ton Diesel — 4x4

Revised – January 2016

**ALERT:** Tractor & Truck pullers hitch opening size requirements: 3 ¾ inch front to back and 3 inch side to side.

1. ENGINE, RUNNING GEAR, AND CHASSIS MUST BE FACTORY ONE TON OR BELOW OR REPLACEMENT. ENGINE SWAPS BETWEEN MANUFACTURERS PERMITTED.
2. DRAWBARS ALLOWED.
3. 26 INCH HITCH HEIGHT. HITCH OPENING SIZE REQUIREMENTS 3 ¾ INCH FRONT TO BACK AND 3 INCH SIDE TO SIDE.
4. DOT TIRES ONLY.
5. EXHAUST MUST EXIT STRAIGHT UP OR STRAIGHT DOWN. MUST HAVE 2 GRADE 5 3/8 BOLTS 1/2 INCH APART 90 DEGREES FROM EACH OTHER AND RECOMMENDED TO BE 12 INCHES FROM EXHAUST IMPELLER.
6. HANGING WEIGHT ALLOWED NOTHING TO EXCEED 60" FROM CENTER OF FRONT AXLE .
7. DRIVE SHAFT LOOPS, U-JOINT SHIELDS, BLOW PROOF BELLHOUSING AND/OR SFI SCATTER BLANKET REQUIRED.
8. AIR SHUT OFF REQUIRED.
9. FIRE EXTINGUISHER REQUIRED!!!!!!
10. ALL PROTESTS MUST BE MADE TO TECH COMMITTEE BEFORE CLASS IS OVER, BY A PARTICIPATE OF THIS CLASS.
11. MODIFIED STREET TRUCKS, **WITH ALL SAFETY EQUIPMENT**, MAY PULL IN THIS CLASS.
12. TRACK AND TECH OFFICIALS DECISIONS ARE FINAL!!!!!!
13. NO PRESSURIZED BOTTLES ALLOWED, INCLUDING NITROUS OXIDE AND PROPANE. **New-01/16**